HYDRAULIC w. sweep

FSI H205 / FSI H40S









Oilflow 30-50

92 kg

SWEEP CONTROL

FSI HxxS model stump cutters are available as controlled directly from the loader/tool carrier (5 hydraulic connectors), or with sweep control by an electronic control box for machines with only 3 hydraulic connectors.



FSI H40S 50-75





Oilflow 50-75

200 kg

FSI H40S 80-110





Oilflow 80-110

250 kg



HYDRAULIC W. SWEEP

Hydraulically driven stump cutter with integrated sweep

Hydraulic driven stump cutter with integrated sweep movement for fitting to loaders and tool carriers. The stump cutter is supplied with an uncoated backplate to which an attachment can be fitted. FSI provides a range of adaptor brackets suitable for the most common tool carriers and loaders upon request.

Two hydraulic cylinders ensure a stable sweeping movement in either direction. Control of the sweeping movement can be done either from the tool carrier or by an electronic control box depending on the connectors available on the tool carrier or loader.

 $FSI\ HxxS\ stump\ cutters\ require\ a\ free-flow\ return\ to\ the\ tank\ (leak\ oil).$

Technical specifications:

Model	H205	H20S-5	H40S 50-75	H40S-5 50-75	H405 80-110	H40S-5 80-110
Power requirements	12-22 /		18-31 /		29-48 /	
(kW/HP)	15-30		25-42		40-65	
Oil flow (I/minute)	30-50		50-75		80-110	
Oil pressure (Max. bar)	250					
Connections	Pressure Return Leak oil	2 x Pressure 2 x Return Leak oil	Pressure Return Leak oil	2 x Pressure 2 x Return Leak oil	Pressure Return Leak oil	2 x Pressure 2 x Return Leak oil
Cutting Head						
Diameter	370 mm		470 mm			
Tooth system	FSI 21 - 3 x rotatable		FSI 25 - 3 x rotatable			
No. of teeth	12		16			
Max cutting depth	2.5 cm per sweep		5.2 cm per sweep			
Cutter wheel drive	Direct Drive					
Uncoated attatchment	Standard					
Dimension						
Lenght (mm)	810 1240					
Width (mm)	69	690 800				
Height (mm)	58	30	720			
Weight (kg)	92		200		250	