

MIDIFORST dt

max. 30 cm Ø 120-190*|240 HP

Strong compact forestry mulcher - the classic!

This forestry machine certainly, punches above its weight with its robust construction.

For a forestry tiller like this, the fixed hammers are the first choice.

The patented rotor shaft and the hammers with additional tungsten carbide inserts make mulching and tilling very efficient. The patented tool holder system allow easy replacement of its hammers for minimum downtime.

Standard version and specifications

- > Mulches bushes and wood up to 30 cm [11.8"]Ø
- > Working speed 0-5 km/h
- > 3 point rear linkage cat. 2 central fixed
- > 1000 rpm gearbox with freewheel
- > Dual side belt transmission
- > Hydraulically operated hood
- > Skids, adjustable in height
- > Front- and rear protection with chains
- > Tempered counter cutters
- > Standard rotor: combination of fixed hammers with tungsten carbide inserts MINI DUO and MONO PROTECT EXTREME

Optional configuration and accessories

- > Combination of fixed hammers with tungsten carbide inserts MONO TIP V-LOCK and MONO PROTECT EXTREME
- > Front attachment
- > Hydraulic top link
- > ADAM™ Alignment system
- > Centrifugal clutch
- > Mechanical or hydraulic guard frame
- > Narrow skids



YouTube www.youtube.com/seppimulcher

Specifications · MIDIFORST dt	Nominal Tractor Power 120-[190*]240 HP		
Working width	200 cm [79"]	225 cm [89"]	250 cm [98"]
Overall width	233 cm [92"]	258 cm [102"]	283 cm [111"]
Depth	125 cm [49"]	125 cm [49"]	125 cm [49"]
Height	115 cm [45"]	115 cm [45"]	115 cm [45"]
Weight (base value w/o options)	1.590 kg [3510lb]	1.930 kg [4250lb]	2.150 kg [4740lb]
Belts	2x5	2x5	2x5
Fixed hammers · MINI DUO + lateral	42+2	46+2	50+2
Fixed hammers · MONO TIP + lateral	61+2	68+2	75+2

* with the optional >centrifugal clutch< the machine is limited to 190HP

Tools



Fixed hammer
MINI DUO



Fixed hammer
MONO TIP V-LOCK





Lateral hammer
EXTREME

MIDIFORST dt · Specifications

Powerful mulcher for tractors between 120 - 240 HP* with reinforced chassis, welded belt protection and lateral deflectors. The machine is completely covered and protected; easy access due to the hatch for service and maintenance.



ADAM™ Alignment system
Angular adjustment protects the PTO shaft and the input shaft.
The range of movement is even greater. (option)



Guard frame for felling operations and to protect the tractor (option)


Machine interior completely covered, accessible via hatch

Lateral material deflectors

Height adjustable skids reinforced by additional steel plates




Heavy chains protect tractor and driver



HELIX ROTOR
CARBIDE

Rotor with fixed hammers, for mulching wood and soil cultivation



COUNTER CUTTERS

Reinforced chassis with wear-resistant steel plates 5 rows of tempered counter cutters for a perfect mulching result