

MIDIFORST

max. 25 cm Ø 80-130 HP

Compact forestry mulcher with high performance

The MIDIFORST forestry mulcher is ideal for a wide range of jobs in forestry: for the care of wood land and forest paths, electricity and gas pipelines, cleaning after the harvesting of wood, for the construction of fire breaks ...

and in agriculture: renewal of existing fruit and wine plants, berry plant and further landscape maintenance.

Standard version and specifications

- > Mulches bushes and wood up to 25 cm [9.8"]Ø
- > Working speed 0-5 km/h
- > 3 point rear linkage cat. 2 central fixed
- > 1000 rpm gearbox with freewheel
- > Belt transmission
- > Hydraulically operated hood
- Reinforced skids, adjustable in height
- > Front- and rear protection with chains
- > Tempered counter cutters
- Standard rotor: combination of fixed hammers with tungsten carbide inserts MINI DUO and MONO PROTECT EXTREME

Optional configuration and accessories

- > Front attachment
- > 3 point rear linkage
- cat. 1 and 2
- > 540 rpm gearbox
- > Centrifugal clutch
- > Guard frame
- > Rake hood
- > Support roller (instead of skids)



YouTube www.youtube.com/seppimulcher

Specifications • MIDIFORST		Tractor 80-130 HP	
Working width	175 cm [69"]	200 cm [79"]	225 cm [89"]
Overall width	204 cm [80"]	229 cm [90"]	254 cm [100"]
Depth	112 cm [44"]	112 cm [44"]	112 cm [44"]
Height	120 cm [47"]	120 cm [47"]	120 cm [47"]
Weight (base value w/o options)	1.240 kg [2730lb]	1.360 kg [3000lb]	1.470 kg [3240lb]
Belts	5	5	5
Fixed hammers · standard	38+2	42+2	46+2



The information in this document is intended as a guide only. SEPPI M. may change their products or their specifications at any time without any obligation of previous notice.

Forestry Mulchers

MIDIFORST · Specifications

Compact strong forestry cutter for medium sized tractors with reinforced chassis, welded belt protection and lateral deflectors.

