

MINIFORST cl

150-350 bar | 50-150 l/min

MINIFORST cl hydraulic transmission mulchers: compact & powerful for compact loaders

These forestry mulchers for skid steers are suitable for forestry work as well as the most demanding applications in landscaping and maintaining areas in which prunings, stumps and wood must be eliminated.

Assembled on a compact loader, they reach hard-to-access areas with great ease.

Standard version and specifications

- > Mulches wood up to 20 cm [8"] Ø
- > Working speed 0-5 km/h
- > Chassis made of high tensile steel S420
- > SAE skid steer attachment interface
- > Belt transmission
- > Pressure gauge
- > Hydraulically operated hood
- > Rear chain protection
- > Support skids
- > Rotor with tungsten CARBIDE inserts hammers MINI DUO; anti-wear hammer support
- > 5 rows of tempered COUNTER CUTTERS (3 chassis, 2 hood)

Optional configuration and accessories

- > Forestry rotor with MINI BLADE
- > MINI BLADE with CUT CONTROL system
- > Without hood
- > Guard frame
- > Electric valve for hood control with controls
- > Variable displacement motor with relief valve
- > M-BOOST™ automatic variable displacement motor
- > Interface plates for loaders
- > 1/2" polycarbonate impact resistant shield for loader. Replaces original glass shield. Excluding installation.



 www.youtube.com/seppimulcher

Specifications · MINIFORST cl

	cm [inch]	150 [59]	175 [69]	200 [79]
Working width	cm [inch]	181 [71]	206 [81]	231 [91]
Overall width	cm [inch]	99 [39]	99 [39]	99 [39]
Depth	cm [inch]	86 [34]	86 [34]	86 [34]
Weight · base value w/o options	kg [lb]	1.055 [2,326]	1.140 [2,513]	1.265 [2,789]
Belts · depending on engine power	qty	4 (5)	4 (5)	4 (5)
MINI-DUO · standard	qty	30	33	36
MINI-BLADE · option	qty	30	33	36

Safety Note: MINIFORST cl may be raised to a maximum of 50 cm [20 inch] and should be only used with stone impact protected cabins.

The information in this document is intended as a guide only. SEPPIM. may change their products or their specifications at any time without any obligation of previous notice.

Extract brochure HYD1-2022-02

Tools



Fixed hammer
MINI-DUO



Fixed hammer
MINI-BLADE

High-performance hydraulic drive



The powerful transmission of the **MINIFORST cl** is compatible with hydraulic systems with flow rates of 50 to 150 l/min and is available with different types of hydraulic motors. The most powerful and efficient motor, the **M-BOOST™** motor, delivers 40% more torque than standard motors.

Your SEPPi M. dealer will help you choose the optimum motor for your application.

HYDRAULIC DRIVE	
Pressure	150-350 bar [2,175-5,075 psi]
Required hydraulic flow	50-150 l/min [13-40 gpm]
Required hydraulic hoses	3 (pressure, return, drainage)
Case drain pressure	max. 1.5 bar

REQUIRED HYDRAULIC FITTINGS	
Hydraulic hood	1 double acting (or OPT-158: electric valve for hood control with controls)

High tensile steel for a light and strong chassis S420

Pressure gauge

Optional guard frame for felling operations and to protect the tractor

Multiple rows of tempered counter cutters for a perfect mulching result
5 COUNTER CUTTERS

Standard rotor: MINI DUO hammer
2 tungsten carbide tips provide high performance and long lifetime
> Efficient on big wood and stumps

Optional rotor: CUT CONTROL system
The sharpenable blade of the MINI BLADE tool with the specially developed gauge reduces the depth of cut
> Fast cut and fine mulch on wood and standing trees

Protected cylinder

Support skids prevent soil penetration; these are specially designed to work in motion and inclination

LOW PROFILE

MINIFORST cl *

* new color combination from 2021